

## **LED** Banner

Ultra-slim integrated design, seamlessly fits into a wide range of applications including retail, exhibitions, and business settings



SPECIFICATIONS		
SKU:	CBLP07219	CBLP07225
LED Size	72"	72"
DISPLAY		
LED Type	SMD	SMD
Application	Indoor	Indoor
Pixel Pitch (mm)	1.9	2.5
Resolution	320 x 900	240 x 675
Orientation	Landscape or Portrait	Landscape or Portrait
Viewing Angle (H)/(V) (°)	160 / 160	160 / 160
View Area (H)/(V)mm	610 x 1715	610 x 1715
Brightness (cd/m2)	800	800
Auto Brightness	Yes	Yes
Contrast Ratio	6500:1	6500:1
Refresh Rate (Hz)	3840	3840
Grayscale (bit)	13-16	13-16
Life of Screen (Hrs)	100,000	100,000
Cabinet Arrangement	5x1	5x1
Hub Design	1 in 3	1 in 3
Bezel	Clip On	Clip On
Advanced Polymer Layer (APL)	Available - add APL to SKU when ordering	Available - add APL to SKU when ordering
Connect Multiple Banners	Up to 6 Banners can be connected	Up to 8 Banners can be connected



## **LED Banner**

Ultra-slim integrated design, seamlessly fits into a wide range of applications including retail, exhibitions, and business settings



SPECIFICATIONS			
SKU:	CBLP07219	CBLP07225	
LED Size	72"	72"	
COMPUTE AND CONTROL			
Operating System	Android	Android	
System Version	Nova Star ViPlex	Nova Star ViPlex	
RAM	1GB	1GB	
ROM	16GB	32GB	
Architecture	Quad Core	Quad Core	
IP Control	Yes	Yes	
Remote Mgt	Yes	Yes	
CommBox Signage	Optional with CommBox Signage Player	Optional with CommBox Signage Player	
POWER			
Avg Power (w)	200	210	
Power Consumption (w)	560	600	
CONNECTIVITY			
WIFI	Yes	Yes	
INPUT AND OUTPUTS			
HDMI In	1	1	
HDMI Out	1	1	
USB A 2.0	1	1	
LAN	1	1	
Audio out - 3.5mm	1	1	



## **LED Banner**

Ultra-slim integrated design, seamlessly fits into a wide range of applications including retail, exhibitions, and business settings



SPECIFICATIONS				
SKU:	CBLP07219	CBLP07225		
LED Size	72"	72"		
STRUCTURE				
Housing	Magnalium	Magnalium		
Product Size (mm)	624 x 1900 x 33.5	624 x 1900 x 33.5		
Product Thickness	33.5	33.5		
Panel Weight (kg)	38	38		
Servicability	Front	Front		
Install Options	Floor, Hanging, Wall	Floor, Hanging, Wall		
ENVIRONMENTAL CONDITIONS				
Operation Temp (°C)	0 - 40	0 - 40		
Operation Humidity (RH)	10%~80%	10%~80%		

WHAT'S IN THE BOX		
Amount	Accessories	
1X	Powercord	
1X	Floor Stand	
1X	Front Maintenace Tool	
1X	Spare Parts and Tool Kits	

## PRE-INSTALLED APPLICATIONS

Nova Star - ViPlex

CERTIFICATIONS		
Certifications	RoHS, RCM, CE	
COMMBOX EXPERIENCE		
Warranty	2 Year Warranty	
Training	Unlimited FREE virtual training	
Support	Same business day help desk support	

<sup>\*</sup>All information and specs contained on this document are correct at time of publication