Infiniti

The ideal screen for large meeting spaces, the Infiniti has an impressive 110-inch screen and has been made to work seamlessly with Microsoft Teams Rooms and Zoom Rooms.

COMBOX

SPECIFICATIONS		
SKU:	CBIIIIO	
LCD Size	110"	
DISPLAY		
Screen Type	LCD	
Glass Type and Thickness	4mm tempered glass - Mohs Level 7	
Glass Protection	Anti-glare 28%	
Backlight Type	D-LED	
Orientation	Landscape	
Aspect Ratio	16:9	
Resolution (H)/(V)	3840x2160	
Android Resolution	4K	
View Area (H)/(V)mm	2436.48 x 1370.52	
Brightness (cd/m2)	450	
Contrast Ratio	1200:1	
LCD Refresh Rate (Hz)	60	
Viewing Angle (°)	178	
Life of Screen (Hrs)	50,000	
Response Time	8ms	
Display Colours (10bit)	1.07	
Colour Gamat	80%	
Bezel Colour	Black/Grey	

Infiniti

The ideal screen for large meeting spaces, the Infiniti has an impressive 110-inch screen and has been made to work seamlessly with Microsoft Teams Rooms and Zoom Rooms.

COMBOX

SPECIFICATIONS	
SKU:	СВІІПО
LCD Size	110"
INTERACTIVITY	
Touch Type	Infrared Recognition
Touch Points	20
Touch Resolution	32767 x 32768
Touch Accuracy	lmm
Response Time	>9ms
Windows with Microsoft Ink Support	Yes - multi-touch
Chromium, Linux	Single-touch
MacOS	Single-touch
Touch Tool	Finger, Passive Stylus, Eraser
Pen Type	2 x Dual Tip Stylus
Pen Tip Diameter	3mm/7mm
Pen & Touch Differentiation	Yes
Pen Holders	Integrated magnetic holders
AUDIO	
Speaker Type	Downward facing
Sound channel	2.1
Speaker (W)	2 x 16W
Subwoofer	16W

Infiniti

The ideal screen for large meeting spaces, the Infiniti has an impressive 110-inch screen and has been made to work seamlessly with Microsoft Teams Rooms and Zoom Rooms.

COMBOX

SPECIFICATIONS	
SKU:	СВІІТО
LCD Size	110"
MICROPHONE	
Line Array	6
Distance of Pick Up (m)	8
COMPUTE AND CONTROL	
Operating System	Windows via the OPS Slot
System Version	Activated Windows 10 Pro License
RAM - OPS	8GB
ROM - OPS	64GB
ARCHITECTURE - OPS	i7 with Quad Core, 1.8GHz, Intel UHD Graphics
RS232 Control	Yes - Baud rate 9200
IP Control	Yes
Wake on Lan	Yes
Remove Device Management	Yes - CommBox Manage can be installed on the Slot-in-PC
POWER	
Power Requirements	240V
Power Consumption w' OPS	800W
Stand by	<0.5W
CONNECTIVITY	
WIFI	Yes on OPS
Bluetooth	Yes on OPS

COMBOX

Infiniti

The ideal screen for large meeting spaces, the Infiniti has an impressive 110-inch screen and has been made to work seamlessly with Microsoft Teams Rooms and Zoom Rooms.

SPECIFICATIONS	
SKU:	СВІПО
LCD Size	110"
INPUT AND OUTPUTS - SCREEN	
Front	
USB-A	2
USB Type-C	1 - Data, 65W charging, Ethernet
USB-B Touch	1
HDMI In	1
Back	
HDMI In	2 x HDMI (2.0)
HDMI Out	1
USB-A 2.0	1
USB-A 3.0	2
USB-B Touch	1
DP In	1
VGA In	1
Audio In	1 - 3.5mm
Audio Out	1
S/PDIF Out	1
RS-232	1
LAN In (RJ45)	1 - 1000MB/sec
LAN Out (RJ45)	1 - 1000MB/sec
OPS Slot	1

COMBOX

Infiniti

The ideal screen for large meeting spaces, the Infiniti has an impressive 110-inch screen and has been made to work seamlessly with Microsoft Teams Rooms and Zoom Rooms.

SPECIFICATIONS	
SKU:	СВІІІО
LCD Size	110"
INPUT AND OUTPUTS - OPS	
USB-A 2.0	1
USB-A 3.0	2
USB-C	2
Headphones + MIC	1
LAN (RJ45 In)	1
HDMI Out	1 (2.0)
WIFI	Yes
Bluetooth	Yes
STRUCTURE	
Housing Material	Aluminium Plate
Product Size (mm)	2507.1 x 1482.1 x 152.9
Package Size (mm)	2800 x 435 x 1550
Net Weight (kg)	134
Gross Weight (kg)	193
VESA (mm)	800 x 1000
Wall-hanging screw spec	M8 x 25mm
ENVIRONMENTAL CONDITIONS (DISPLAY + WIFI MODULE)	
Operation Temperature (°C)	0 - 40
Operation Humidity (RH)	10% - 90%
Altitude (m)	Below 5000

Infiniti

The ideal screen for large meeting spaces, the Infiniti has an impressive 110-inch screen and has been made to work seamlessly with Microsoft Teams Rooms and Zoom Rooms.

COMBOX

SPECIFICATIONS

WHAT'S IN THE BOX	
Amount	Accessories
2X	AAA Batteries
١X	Remote
2X	Stylus
١X	3M powercord - AU/NZ
١X	3M USB A-B touch cable
١X	3M HDMI cable
1X	CommBox Eraser
١X	Wall Bracket and Mounting Kit
١X	Slot-in-PC i7

COMMBOX EXPERIENCE		
Warranty	5 Year Warranty	
Training	Unlimited FREE virtual training for the life of the screen	
Support	Same business day help desk support	

*All information and specs contained on this document are correct at time of publication