LEGENDARY SOUND. RIGHT OUT OF THE BOX.

BLX® WIRELESS SYSTEMS



BLX® Wireless Systems WIRELESS FREEDOM, MADE SIMPLE.

Making the jump to wireless should be liberating, not challenging. Shure BLX Wireless Systems combine professional quality sound with simple setup and an intuitive interface for performance you can trust right out of the box. Precision built and available in a variety of handheld, lavalier, instrument and headset configurations, it's the most accessible way to own the stage.

SYSTEM COMPONENTS

BLX4, BLX4R and BLX88 Diversity Receivers

- Up to 12 compatible systems per frequency band (region dependent)
- Microprocessor-controlled internal antenna diversity
- One-touch QuickScan frequency selection quickly locates the best frequency
- 1/4" and XLR audio outputs
- Two color audio status indicator LED

Wireless Transmitters

- Power and battery status LED
- Adjustable gain control
- Quick & easy frequency matching
- 2 AA batteries (included) provide up to 14 hours of continuous use
- 300 feet (91 m) operating range (line of sight)



SHURE Adda mady program channel and and program channel bit of the state of the sta

BLX88 Dual Wireless Receiver



VOCAL

For lead and backup vocals.



PG58 CARDIOID | DYNAMIC Professional-quality microphone capsule for lead and backup vocal performance applications

WITH BLX4 OR BLX88

SM**58**°

CARDIOID | DYNAMIC Industry-standard microphone capsule tailored to deliver warm, clear vocal reproduction



WITH BLX4 OR BLX4R

BETA 58A° SUPERCARDIOID DYNAMIC

Precision-engineered microphone capsule optimized for lead vocal applications

WITH BLX4 OR BLX4R

Optional Accessory: 5 Color ID Caps for handheld transmitter



BLX1 BODYPACK SYSTEM OPTIONS

GUITAR

For guitar or bass.



WA302 GUITAR CABLE 1/4"-to-TA4F instrument cable to connect transmitter to a guitar or bass

WITH BLX4 OR BLX4R

INSTRUMENT

For brass, wind, and percussion instruments.



BETA 98H/C CARDIOID | CONDENSER Precision-crafted, flexible

WITH BLX4 OR BLX4R

HEADSET

For vocalists, presenters, aerobics instructors and drummers.



PGA31 CARDIOID | CONDENSER

Comfortable, durable head-worn microphone for active performance applications

WITH BLX4, BLX4R OR BLX88

SM31FH CARDIOID | CONDENSER

Rugged, comfortable head-worn microphone with increased moistureresistance for active speech and fitness applications

WITH BLX4, BLX4R OR BLX88

SM**35**

CARDIOID | CONDENSER Rugged, comfortable head-worn microphone for roadworthy, high-quality live vocal performance applications

WITH BLX4, BLX4R OR BLX88

PRESENTER

For presenters, instructors, teachers and clergy.





Reliable wearable microphone for spoken word applications



WITH BLX4, BLX4R OR BLX88

W**∟93** OMNIDIRECTIONAL CONDENSER

Miniature wearable microphone for spoken word applications



WITH BLX4R

WL185 CARDIOID | CONDENSER

Premium wearable microphone optimized for spoken word applications



WITH BLX4R

MX153

OMNIDIRECTIONAL CONDENSER

Premium sub-miniature earset microphone for discrete, exceptional clarity in spoken word applications



WITH BLX4R





gooseneck instrument microphone for brass, woodwind, and percussion applications



BLX® Wireless Systems

BLX2 HANDHELD SYSTEM OPTIONS

BLX1 BODYPACK SYSTEM OPTIONS

Model

GUITAR

WA302

PGA31

40Hz – 20kHz

WL93

PRESENTER

50Hz – 20kHz

MX153

PRESENTER

20Hz-20kHz

Operating Principle

 \bigcirc ())

(=)

Dynamic 😑 Condenser

HEADSET

Model	Includes
BETA 58A° VOCAL 50Hz-16kHz	 BETA 58A® Handheld Microphone with BLX2 Transmitter BLX4 or BLX4R Wireless Receiver Durable Padded Zipper Case Break-resistant Microphone Clip 2 AA Batteries
PG 58 vocal	PG58 Handheld Microphone with BLX2 Transmitter BLX4 or BLX88 Wireless Receiver
60Hz – 15kHz	Break-resistant Microphone Clip 2 AA Batteries

Cardioid

SuperCardioid ()OmniDirectional

Model	Includes	
SM58°	SM58 [®] Handheld Microphone with BLX2 Transmitter	
VOOAL	 BLX4 or BLX4R Wireless Receiver 	
50Hz – 15kHz	 Durable Padded Zipper Case 	
∞ 🖗 🔛	 Break-resistant Microphone Clip 	
	• 2 AA Batteries	

BLX1 BODYPACK SYSTEM OPTIONS

Break-resistant Microphone Clip 2 AA Batteries	Model	Includes
TEM OPTIONS Includes	BETA 98H/C INSTRUMENT 20Hz - 20kHz () (=) ())	 BETA 98H/C Instrument Microphone BLX1 Bodypack Transmitter with 2 AA Batteries (included) BLX4 or BLX4R Wireless Receiver Durable Padded Zipper Case
 •WA302 Guitar Cable •BLX1 Bodypack Transmitter with 2 AA Batteries (included) •BLX4 or BLX4R Wireless Receiver • Durable Padded Zipper Case 	CVL PRESENTER 60Hz-12kHz	 CVL Lavalier Microphone BLX1 Bodypack Transmitter with 2 AA Batteries (included) BLX4, BLX4R OR BLX88 Wireless Receiver Tie Clip and Windscreen
 PGA31 Headset Microphone BLX1 Bodypack Transmitter with 2 AA Batteries (included) BLX4, BLX4R OR BLX88 Wireless Receiver Windscreen 	WL185 PRESENTER 50Hz-20kHz	 WL185 Lavalier Microphone BLX1 Bodypack Transmitter with 2 AA Batteries (included) BLX4R Wireless Receiver Durable Padded Zipper Case Tie Clip and Windscreen
 WL93 Lavalier Microphone BLX1 Bodypack Transmitter with 2 AA Batteries (included) BLX4R Wireless Receiver Durable Padded Zipper Case Tie Clip and Windscreen 	SM31FH HEADSET 40Hz-20kHz	 SM31FH Headset Microphone BLX1 Bodypack Transmitter with 2 AA Batteries (included) BLX4, BLX4R OR BLX88 Wireless Receiver Windscreen
 MX153 Earset Microphone BLX1 Bodypack Transmitter with 2 AA Batteries (included) BLX4R Wireless Receiver Durable Padded Zipper Case Collar Clip, Windscreen, and Protective Pouch 	SM35 HEADSET 40Hz-20kHz	 SM35 Headset Microphone BLX1 Bodypack Transmitter with 2 AA Batteries (included) BLX4, BLX4R OR BLX88 Wireless Receiver Windscreen
Polar Pattern	Fr	requency Response

Flat Tailored

TECHNICAL SPECIFICATIONS

Operating Range:

300 ft (91 m) line of sight (actual range depends on RF signal absorption, reflection and interference)

Available Frequencies: Between 524-865 MHz (available frequencies depend

on applicable regulations in country where system used) Audio Range:

50-15,000 Hz

(dependent on microphone type)

Transmitter RF Output Power: 10 mW, typical (varies by region)

Audio Output Connector: XLR and 1/4" (6.3 mm)

unbalanced

Maximum Output Level: -27 dBV (XLR, mic level), -13 dBV (1/4")

Battery Life: Up to 14 hours

Dynamic Range:

100 dB A-weighted

System Distortion: 0.5% THD typical

(ref. +/- 38 kHz deviation, 1 kHz tone)

Operating Temperature Range: -18°C (0°F) - +50°C (122°F)

Power Requirements: BLX1, BLX2: 2 AA alkaline or rechargeable batteries

BLX4: 12-18 V DC at 150 mA, supplied by external power supply

BLX88: 12-18 V DC at 320 mA, supplied by external power supply

BLX4R: 12-18 V DC at 260 mA, supplied by external power supply

Note: Performance may vary depending on country regulations and operating environment.

