imagePROGRAF TA SERIES SPECIFICATIONS

PRINTERS

24" TA-20 36" TA-30

PRINT HEAD

PF-06

TECHNOLOGY

FINE (Photolithography Inkjet Nozzle Engineering)

PRINT RESOLUTION (MAX.)

2400 x 1200 dpi

NUMBER OF NOZZLES

Matte Black: 5,120 Nozzles Other Colours: 2,560 Nozzles per Colour

INK TYPE

Pigment: Matte Black (MBK), Cyan (C), Magenta (M),

Yellow (Y), Black (BK)

INK TANK
Shipped with Printer: BK, C, M, Y (55 ml), 2 x MBK

(2 x 55 ml, Total 110 ml) **Replacement:** PFI-030 (55 ml)

NOZZLE RECOVERY SYSTEM

Non-firing Nozzle Detection and Compensation

PRINTER CONTROLLER

L-COA PRO

PRINTER RAM

2 GB

MEDIA FEED

Roll Feed: One Roll, Top-loading, Front Output

CUT SHEET

Top-loading, Front Output (Manual feed using media locking lever)

MEDIA WIDTH

TA-20: 8"–24" (203 mm – 610 mm) **TA-30:** 8"–36" (203 mm – 914 mm)

PRINTABLE MARGINS

Roll Feed: All Sides: 3 mm or 0" for Borderless

CUT SHEET

Top: 3 mm, Bottom: 20 mm, Side: 3 mm

MAXIMUM PRINT LENGTH (SINGLE PAGE)1

Roll Feed: 18 m Cut Sheet: 594 mm SIZE/WEIGHT (WxDxH)

TA-20 (Without Stand):

982 x 748 x 438 mm; Approx. 37 kg **TA-30 (With Stand, Basket Open):**

1,289 x 870 x 1,059 mm; Approx. 53 kg

OPTIONS

TA-20 2"/3" Roll Holder Set (RH2-28) TA-30 2"/3" Roll Holder Set (RH2-35)

PosterArtist

TA-20 Stand (SD-24)
User Replaceable Items:

Ink Tank (PFI-030)

Print Head (PF-06)

Maintenance Cartridge (MC-31)

Cutter Blade (CT-08)

1 The maximum printable length varies depending on the application. OS. and RIP used.

At Canon we've always been about improving outcomes for your business. So get in touch with us today at **1800 444 199** or visit **canon.com.au/large-format-printers** to find out which professional imaging solutions are going to be the right fit for your business.



