

Model	
Model	LM250
Short Description	250W LED Spot Moving Head
Photometrics	
Light Source	250W LED 7500K
Beam Angle	12°-36°
Output	31,600 lux @ 2.5 m @ 12°
Effects	
Dimming	0-100%, 8/16-bit
Strobe	1.2-25 Hz
Focus	2.5-15m, linear via DMX
Prism	3-facet
Frost	Yes
Iris	Yes
Movement	
Movement	8/16-bit, auto-reposition
Pan	360°/540°/630°
Tilt	90°/180°/270°

Colour Wheel Colour Wheel Fixed Gobo Wheel Rotating Gobo Wheel Colour CTB Colour CTB

Colour	
Colour Wheel	7 + open
Gobos	
Fixed Gobo Wheel	11 + open
Rotating Gobo Wheel	6 + open (interchangeable, outside Ø22.9mm, inside Ø18mm)
Power	
Connection	PowerCON in/out
Power Consumption	320W
Control	
Operation Modes	DMX, manual, auto, sound active, master/slave
Control Protocol	DMX512
DMX Channels	14/16/18
Control Interface	3-pin XLR in/out
Display	4-button 2.4" TFT LCD control panel
Housing	
Materials	Metal and flame retardant ABS, matte black finish
Cooling	Fan

Scan for more info:



Lux Chart @ 12°			
2.5m	5m	7.5m	10m
Ø0.53	Ø1.05	Ø1.58	Ø2.1
41,550	11,940	5,350	3,150

Lux Chart @ 36°				
2.5m	5m	7.5m	10m	
Ø1.62	Ø3.25	Ø4.87	Ø6.5	
5,230	1,450	850	400	

IP Rating	IP20
Net Weight	14 kg
Rigging	2x omega brackets with 1/4 turn quick locks
Box Dimensions	430 x 410 x 530 mm
Accessories	
Optional Accessories	Road Case: LM2CASEVL, Wireless DMX: WDMXLM

