

RGBlink vue PTZ camera



Front View



Rear View



Left View

Key Features

- High speed optical zoom
- RTSP/RTMP/SRT encoding output
- High performance in low light scenarios with wide dynamic range
- Full 1920x1080p HD resolutions up to 60 frames per second
- H.265/H.264 dual stream output adapted to different network environments
- Pan and Tilt control

- 12X/20X/30X optical zoom
- NDI | HX output for PNDI model camera
- Applicable to meeting, live streaming, church, classroom and more
- Low-power Sleep Function
- Support TALLY
- Support PoE

Specification

Interface	Output	3G SDI HDMI USB LAN	1xBNC 1xHDMI-A 1xUSB-A 1xRJ45	
	Audio	IN	1x3.5mm Stereo Jack	
	Control	RS232 IN/OUT RS485	2xDIN8 1x4pin Terminal	
	Power		1xDC12V Jack	
Performance	Camera		12X 20X 30X f=4.1~49.2mm f=4.8~96mm f=5.2~148.4mm View Angle 6.57°~ 70.28° 3.45°~ 60.04° 2.14°~58.1° AV F1.8 ~ F2.68 F1.8 ~ F2.9 F1.3 ~ F4.8 Digital Zoom 10X Minimum Illumination 0.5Lux (F1.8, AGC ON) DNR 2D & 3D DNR White Balance Auto/Manual/One Push/3000K to 7000K(selectable) Focus Auto/Manual Aperture/Electronic Shutter Auto/Manual BLC ON/OFF WDR OFF/Dynamic Level Adjustment Video Adjustment Brightness/Color/Saturation/Contrast/Sharpness/B/W mode/Gamma curve SNR >55dB Effective Pixels 2.07 megapixels Sensor 1/2.8 inch HD CMOS Sensor	
	Pan-and-Tilt Parameter	Pan/Tilt Movement Pan/Tilt Control Speed Preset Speed/Quantity 360° TALLY	-170°~+170°/-30°~+90° 0.1~60°/S; 0.1~30°/S Pan:60°/S, Tilt:30°/S; Up to 255 preset positions (10 remote control) full 360° view of TALLY	
	Audio Compression Format	AAC MP3 G.711A		
	Video Compression Format	H.264 H.265 Dual Streaming Output		
	Output Resolutions	1080p60/59.94/50/30/29.97/25 1080i60/59.94/50 720p60/59.94/50		
	Control Protocol	VISCA Pelco-D Pelco-P ONVIF		
	Baud Rate(bps)	115200 9600 4800 2400bps		
	Network Protocol	RTSP RTMP ONVIF		
	Supported Standards	SDI SMPTE 425M (Level A & B) SMPTE 424M SMPTE 292M SMPTE 259M-C DVB-ASI		
	Power	Input Voltage	DC12V/1.5A	
		Max Power	12W	
	Environment	Temperature	-10℃~50℃	
		Humidity	20%~80%	
	Physical	Weight	Net	1.7kg
	Dimension	Net	180mm(front)×188mm(side)×198mm(height)	

Order Codes

Product Code	Item
981-0011-27-0	RGB20X-PoE-TLY, 20X PTZ Camera with TALLY (Support PoE)
981-0011-28-0	RGB20X-PNDI-TLY, 20X NDI Camera with TALLY (Support PoE)
981-0011-29-0	RGB20X-USB-TLY, 20X USB PTZ Camera with TALLY
981-0011-31-0	RGB12X-PoE-TLY, 12X PTZ Camera with TALLY (Support PoE)
981-0011-32-0	RGB12X-PNDI-TLY, 12X NDI Camera with TALLY (Support PoE)
981-0011-33-0	RGB30X-PoE-TLY, 30X PTZ Camera with TALLY (Support PoE)
981-0011-34-0	RGB30X-PNDI-TLY, 30X NDI Camera with TALLY (Support PoE)

Specifications are correct at time of printing and subject to change or alteration without notice.

